




## Vacuum Pump V-300 / V-600

### Technical data sheet

The Vacuum Pump V-300 and the Vacuum Pump V-600 are chemically resistant PTFE diaphragm pumps. The speed-controlled operation in conjunction with the Interface I-300 / I-300 Pro results in economical operation and very low noise emission. Thanks to the transparent front panel, contaminants are easily visible. It is optimally suited to work with the I-300 / I-300 Pro and R-300.



## Vacuum Pump V-300 / V-600

Two recommended solutions, "Rotavapor® Dynamic Pro" and "Rotavapor® Dynamic", with the Vacuum Pump V-300 in combination with the Rotavapor® R-300, the Interface I-300 / I-300 Pro and the Recirculating Chiller F-308 can be found in the technical datasheet of the Rotavapor® R-300 "Exemplary solution" and in the "Laboratory Rotary Evaporation Solutions" brochure.

All accessories and connections are included for out of the box usage.

### Available instruments

### Recommended vacuum system

R-300 without Interface I-300 / I-300 Pro, without VacuBox, without Woulff bottle

V-300 with I-300, VacuBox and Woulff bottle

R-300 with I-300 / I-300 Pro and VacuBox and Woulff bottle

V-300

## Order Code

Choose the configuration according to your needs:

1 1 V 0 0 0

### Vacuum Pump

- 3 V-300 (5 mbar, 1.8 m<sup>3</sup>/h)
- 6 V-600 (1.5 mbar, 3.1 m<sup>3</sup>/h)

### Interface

- 0 Without
- 1 Without, with Woulff bottle
- 2 Interface I-300, with Woulff bottle (incl. VacuBox)
- 3 Interface I-300 Pro, with Woulff bottle (incl. VacuBox)
- 8 Without, for R-220 Pro\*

### Condensation assembly

- 0 Without
- 1 Secondary condenser with insulation
- 2 Secondary cold trap

\* For V-600 only

## Scope of delivery

All configurations are supplied ready to use.

Component	V-300	V-600
Vacuum Pump V-300	1	
Vacuum Pump V-600		1
Vacuum tubing	1	1
Power cable	1	1
Silencer	1	1
Tubing connections (set)	1	1
Communication cable (Mini-DIN)	1	1
Membrane tool (to fasten and remove membrane)	1	1
Interface I-300 / I-300 Pro (incl. holder)	*	*
Woulff bottle	*	*
VacuBox (incl. communication cable)	*	*
Accessories needed for R-220 Pro	-	*
Condensation assembly	*	*

\* Optional, according to order code

## Technical data

### Vacuum Pump

Specification	V-300	V-600
Dimensions (W x D x H)	200 x 321 x 291 mm	330 x 321 x 291 mm
Dimensions (W x D x H)	585 x 385 x 370 mm	585 x 385 x 370 mm
Shipping box without secondary assembly		
Dimensions (W x D x H)	585 x 385 x 540 mm	585 x 385 x 540 mm
Shipping box with secondary assembly		
Weight	7.6 kg	13.9 kg
Suction capacity	1.8 m³/h	3.1 m³/h
Number of steps (heads)	2 (2)	3 (4)
Final vacuum (absolute)	5 mbar (± 2 mbar)	1.5 mbar (± 1 mbar)
Vacuum connection	GL14	GL14
Power consumption	180 W	360 W
Power consumption, energy saving mode 1 (80%)	95 W	190 W
Power consumption, energy saving mode 2 (50%)	60 W	120 W
Power supply voltage	100 – 240 VAC	100 – 240 VAC
Frequency	50/60 Hz	50/60 Hz
Maximum speed	1500 rpm	1500 rpm
Sound level (depending on operating mode)	32 – 57 dBA	40 – 64 dBA
Sound level with 10 % load (normal)	32 dBA	40 dBA
Sound level with 100 % load	57 dBA	64 dBA
Overvoltage category	II	II
IP Code	IP20	IP21
Pollution degree	2	2
Inlet temperature of media in ATEX 3G T3 IIC X operation mode	< 40 °C	< 40 °C
Ignition temperature of media in ATEX 3G T3 IIC X operation mode	> 200 °C	> 200 °C
Approvals	CE / CSA / CUS	CE / CSA / CUS

## Special features

### Vacuum Pump

#### V-300 / V-600

Inspection window	A large glass window at front side Allows to observe the two pump heads and membranes for eventual dirt particles
Power saving mode (without I-300 / I-300 Pro)	Pump automatically switches to power saving mode after a given operation time Reduces power consumption while maintaining same terminal vacuum
Level sensor (in combination with Interface I-300 / I-300 Pro only)	Warns of overflow into receiving flask of condenser/secondary condenser When solvents reaches a certain level, a warning pops up at interface and is sent to smartphone/tablet
Control two Rotavapor® systems in parallel	Operate two systems (in combination with 2 Interface I-300 / I-300 Pro only) Allows an upgrade to control two vacuum sources with two Rotavapor® systems simultaneously

## Compatibility and communication requirements with a V-300 / V-600

Interface / Vacuum Controller	Compatibility / Mode	Communication requirements
I-300 / I-300 Pro	compatible speed controlled	VacuBox 2x Communication cable. BUCHI COM 6p: 11058705 (0.3 m), 11058707 (1.8 m), 11058708 (5 m) or 11064090 (15 m)
I-100	compatible on/off	Communication cable. Mini-DIN 8p: 11060882 (0.6 m) or 038010 (1.5 m) Power adapter (11060699)
V-850 / V-855	compatible speed controlled	Communication cable. Mini-DIN 6p to RJ45 11060649 (1.5 m) or 11064104 (3 m)
V-800 / V-805	compatible on/off	Communication cable. Mini-DIN 8p 11060882 (0.6 m) or 038010 (1.5 m) Power cable 2p (1.8 m)

## Explanation of terms

speed controlled	Vacuum pump is turned on/off as well as speed controlled via interface/vacuum controller.
on/off	Vacuum pump is automatically turned on/off via interface/vacuum controller

A VacuBox is included when ordering Rotavapor® R-300 with an Interface I-300 or Interface I-300 Pro compatibility pack.

## Feature comparison (V-300 / V-600 and Interface)

Vacuum Pump features	I-300 Pro / I-300	I-100	V-850 / V-855	V-800 / V-805	Without in- terface
Power saving mode					●*
Speed control	●		●		
Level sensor for receiving flask	●				

Generic features	I-300 Pro / I-300	I-100	V-850 / V-855	V-800 / V-805	Without in- terface
Live data charting	only I-300 Pro				
Leak test	•				
Dynamic distillation (only when connected with Rotavapor® R-300)	•				
Solvent Library	•		•		
Data recording	only I-300 Pro		Optional via PC SW		
Guided operation (methods)	only I-300 Pro		gradients	gradients	
AutoDest	•		•	•	
Timer	•	•	•	•	

\* System without the interface runs autonomously.

## Description of function

The diaphragm pump is a positive displacement pump that uses a combination of the reciprocating action of a PTFE diaphragm and non-return check valves. The eccentric module lets the diaphragm move strictly axial which leads to an increased service life.


### Energy saving mode

This power saving mode is automatically activated in unregulated operation (as a standalone, without an Interface I-300 or I-300 Pro), hence the pump does not work at its full capacity. The energy saving mode is activated after 1 hour of operation, where the pump works at 80 %. After 2 hours, it reduces to 50 %. In the energy saving mode the pump consumes less electrical power and works under reduced stress, accordingly, the overall maintenance costs will be reduced over the lifetime of the pump.




### Performance characteristics

The V-300 and V-600 have a good suction capacity also at a low pressure. The graphs in the top row show suction capacity against pressure. The graphs in the bottom row show the evacuation time of a laboratory evaporator (left side) and an industrial evaporator (right side).

V-300



V-600



Upgrades

Upgrade the Vacuum Pump V-300 / V-600 to a speed controlled vacuum source


The Vacuum Pump V-300 / V-600 can easily be upgraded to a controlled vacuum source by adding the Interface I-300 / I-300 Pro (incl. VacuBox and Woulff bottle).

Upgrade the Vacuum Pump V-300 / V-600 to operate with 2 Rotavapor® systems

The Vacuum Pump V-300 / V-600 can easily be upgraded to work with two vacuum loads via Interface I-300 / I-300 Pro simultaneously (on/off communication, not speed controlled).

Accessories

Communication cables

	Order no.	Image
Communication cable. BUCHI COM, 0.3 m, 6p	11058705	
Enables connection between Rotavapor R-300 / R-220 Pro, Interface I-300 / I-300 Pro, Vacuum Pump V-300 / V-600, Recirculating Chiller F-3xx, VacuBox and LegacyBox.		



	Order no.	Image
<p>Communication cable. BUCHI COM, 1.8 m, 6p</p> <p>Enables connection between Rotavapor R-300 / R-220 Pro, Interface I-300 / I-300 Pro, Vacuum Pump V-300 / V-600, Recirculating Chiller F-3xx, VacuBox and LegacyBox.</p>	11058707	
<p>Communication cable. BUCHI COM, 5.0 m, 6p</p> <p>Enables connection between Rotavapor R-300 / R-220 Pro, Interface I-300 / I-300 Pro, Vacuum Pump V-300 / V-600, Recirculating Chiller F-3xx, VacuBox and LegacyBox.</p>	11058708	
<p>Communication cable. BUCHI COM, 15 m, 6p</p> <p>Enables connection between Rotavapor R-300 / R-220 Pro, Interface I-300 / I-300 Pro, Vacuum Pump V-300 / V-600, Recirculating Chiller F-3xx, VacuBox and LegacyBox.</p>	11064090	
<p>Communication cable. Mini-DIN 6p to RJ45, 1.5 m</p> <p>Connection between Vacuum Controller V-850 / V-855 and Vacuum Pump V-300 / V-600 or between Vacuum Controller V-850 / V-855, Interface I-100 and Recirculating Chiller F-305 / F-308 / F-314.</p>	11060649	
<p>Communication cable. Mini-DIN 6p to RJ45, 3 m</p> <p>Connection between Vacuum Controller V-850 / V-855 and Vacuum Pump V-300 / V-600 or between Vacuum Controller V-850 / V-855, Interface I-100 and Recirculating Chiller F-305 / F-308 / F-314.</p>	11064104	
<p>Communication cable. Mini-DIN, Y-piece, 2.0 m</p> <p>Meant to be used with 1 Vacuum Pump V-300 and 2 Rotavapor systems with the Interface I-300/I-300 Pro. Connection between VacuBox and Vacuum Pump V-300.</p>	11062255	

## Tubing

	Order no.
<p>Tubing. FEP, Ø6/8 mm, transparent, per m</p> <p>Use: Vacuum, cooling media.</p>	027900
<p>Tubing. Natural rubber, Ø6/16 mm, red, per m</p> <p>Use: Vacuum.</p>	017622
<p>Tubing. Nylflex, PVC-P, Ø8/14 mm, transparent, per m</p> <p>Use: Vacuum, cooling media, feeding (industrial Rotavapor®).</p>	004113
<p>Tubing. PTFE, Ø8/10 mm, white, per m</p> <p>Use: Vacuum, feeding (industrial Rotavapor®).</p>	027277
<p>Tubing. Silicone, Ø6/9 mm, transparent, per m</p> <p>Use: Cooling media.</p>	004133

	Order no.
Tubing. Synthetic rubber, Ø6/13 mm, black, per m	11063244
Use: Vacuum.	

## Other accessories

	Order no.	Image
Fastening set. For VacuBox, incl. holder 2 pcs, tube Used to fasten VacuBox on the Vacuum Pump V-300 or V-600.	11062957	
Holder, set. To fix V-8xx, I-100 or Manometer on V-300 / V-600 Used to mount Vacuum Controller V-8xx, Manometer or Interface I-100 on the Vacuum Pump V-300 / V-600. Content: rod and intermediate plate.	11065224	
Holder set. For V-7xx secondary condenser on V-300 / V-600 Used to mount V-7xx secondary condenser on the Vacuum Pump V-300 or V-600.	11065095	
Level sensor. Incl. O-ring, cable, rubber band Prevents an overflow in the receiving flask of condenser/secondary condenser. Placed on receiving flask. Meant to be used with the Interface I-300 / I-300 Pro.	11060954	
Membrane clamp. Incl. torx wrench TX25, TX10 To fasten and remove membranes.	11062343	
Secondary condenser C, set. Cold trap P+G-LT, incl. V-300 holder Condenses remaining vapors after the vacuum pump outlet. Application temperature: -70 to 40 °C. Used with ice/dry ice. Content: Cold trap P+G-LT, 500 mL receiving flask, ball joint clamp, V-300 holder. Compatible with V-300 and V-600 vacuum pumps.	11060050	
Secondary condenser V, set. Glass condenser, incl. insulator and V-300 holder Condenses remaining vapors after the vacuum pump outlet. Used along with a recirculating chiller or tap water. Content: glass condenser, receiving flask 500 mL, insulator for condenser, ball joint clamp, V-300 holder. Compatible with V-300 and V-600 vacuum pumps.	11059900	
Valve unit. Incl. Wouff bottle, 125 mL, P+G, holder Magnetic valve, meant to be used with the Interface I-300/I-300 Pro. For operation with non-BUCHI vacuum pumps or house vacuum.	11061887	

	Order no.	Image
Woulff bottle. 125 mL, P+G, incl. holder For trapping particles and droplets and for pressure equalization.	11059905	

## Receiving flask




	Order no.
Glass, SJ35/20, 250 mL, P+G	11060907
Glass, SJ35/20, 250 mL	000423





## Wearing parts

### Seals




	Order no.
Gasket. Flat gasket, silicone, PTFE	047165
Seal. For cap nut GL14 to FEP, EPDM	038225
Seals, set. 10 pcs, for hose barbs GL14, EPDM, black	040029
Seals, set. 10 pcs, for hose barbs GL14, FPM, green	040040
Seals, set. 10 pcs, for hose barbs GL14, silicone, red	040023







### Hose barbs

	Order no.	Image
Hose barbs. set. 3 pcs, bent, GL14, silicone seal Content: Hose barbs, seals.	041987	
Hose barbs, set. 4 pcs, bent GL14, silicone seal Content: Hose barbs, cap nuts, seals	037287	
Hose barbs. set. 4 pcs, bent, GL14, EPDM seal Content: Hose barbs, cap nuts, seals.	043129	

	Order no.	Image
Hose barbs. set. 4 pcs, bent, GL14, FEP seal Content: Hose barbs, cap nuts, seals.	040295	
Hose barbs. set. 4 pcs, straight, GL14, EPDM seal Content: Hose barbs, cap nuts, seals.	043128	
Hose barbs. set. 4 pcs, straight, GL14, FPM seal Content: Hose barbs, cap nuts, seals.	040296	
Hose barbs. set. 4 pcs, straight, GL14, silicone seal Content: Hose barbs, cap nuts, seals	037642	
Hose barbs. set. 6 pcs, bent (4), straight (2), GL14, silicone seal Content: Hose barbs, cap nuts, seals.	038000	

## Miscellaneous wearing parts

	Order no.	Image
Cap nuts, set. 10 pcs, screw cap with hole GL14, seal EPDM Content: Cap nuts, seals	041999	
Cap nuts. set. 10 pcs, screw cap with hole, GL14	041956	
Membrane, set. 2x, for V-300 / V-600, V-100, V-7xx Content: 2 membranes with support rings and 1 membrane clamp.	11065776	

	Order no.	Image
O-ring. For secondary condenser, FKM/FEP, Ø28.2/2.6 mm	11057661	
Screw caps. set. 5 pcs, GL14	040624	
Set gas ballast. Incl. gas ballast, clip, lever	11062527	
Screwing set, Hose barbs and seals GL14 Content: Hose barbs bent 4 pcs, hose barbs straight 1 pc, cap nuts 4 pcs, screw caps 2 pcs, seals EPDM 3 pcs.	11061921	
Set wear part. Membranes, hose barbs Content: Membrane 4 pcs, support ring 4 pcs, set valve, tube intake, tube connection, tube exhaust, tube elbow, T-connector, set hose barbs (11061921). For use with Vacuum Pump V-600.	11065180	
Set wear part. Membranes, hose barbs Content: Membrane 2 pcs, support ring 2 pcs, valve 4 pcs, tube intake, tube connection, tube exhaust, elbow fitting 4 pcs, set hose barbs (11061921). For use with Vacuum Pump V-300.	11062525	

## Additional glassware

Additional glassware like evaporating flasks, drying flasks, receiving flasks, beaker flasks, Reitmeyer adapters (bump traps) and distillation spiders can be found in the Laboratory Evaporation Glassware brochure.